# **Peerless<sup>®</sup> Boilers**

# Peerless® PureFire® PeerlessBoilers.com High Efficiency Condensing Gas Boilers

#### **Features and Benefits**

- ✓ Up to 96.5% efficiency!
- ✓ ENERGY STAR® Certified!\*
- ✓ Gas-fired Condensing Boiler for Natural or LP Gas
- ✓ **9 Sizes Available -** Residential and Commercial
- ✓ Direct-vent, Sealed Combustion
- **✓ Fully Modulating Burner for Maximum Efficiency**
- ✓ Factory Tested, Pre-Mixed Gas Burner Technology
- ✓ ETL Certified for U.S. and Canada
- ✓ **Environmentally Friendly -** LoNOx Operation
- ✓ Sleek, Modern Design with Easy Access to Controls
- ✓ Compact, Lightweight and Small Footprint
- ✓ Cascade Capable up to 16 Boilers

\*not including PF-300 model



# PF TO PFW CONVERSION KIT

Turn the PF-200 or PF-399 into a PFW-200 or a PFW-399 large volume, hot water supply boilerwith our simple conversion kit!



SCAN FOR PUREFIRE® PRODUCT INFO

#### **Standard Equipment**

- ✓ Built-in Condensate Neutralizer System with Float Switch Protection
- ✓ State-of-the-Art Control Board with Advanced Features
- ✓ High Grade Stainless Steel Burner & Heat Exchanger
- ✓ Outdoor Reset Capability
- ✓ Domestic Hot Water Priority
- ✓ PVC Screened Air Intake & Exhaust
- ✓ Combination Temperature-Pressure Gauge & 30 PSIG Relief Valve





- Supply/Return Pipes
- 2 Boiler Status Display
- **3** Blower
- **4** 120V Service Outlet
- **5** Top Vent Connections
- **6** Service Switch
- **7** Reliable Dual Flame Sensors
- **8** Condensate System with Neutralizer
- **9** Leveling Legs



The PUREFIRE® boiler includes a 12-year residential limited warranty on the heat exchanger. A five-year parts and one-year labor warranty is also included (labor coverage starting on day 91; boiler must be registered for parts/labor warranty to take effect). Visit PeerlessBoilers.com for WARRANTY complete details.

PeerlessBoilers.com

# Technical Information Peerless® PureFire® High Efficiency Condensing Gas Boilers

### **Carton Dimensions** & Shipping Weights


	Boiler Model Number	Length	Width	Height	Approx Shipping Weight (Lbs)
RESIDENTIAL	PF-50/PF-80	21"	16"	36"	88
	PF-110/PF-140	21"	23"	36"	108/118
	PF-200/PF-210	21"	24"	48"	165
COMMERCIAL	PF-300 PF-399 PFC-460	25"	32"	50"	255











# Boiler Ratings AMERICANTIFIED


	Boiler Model	Input (MBH)		Heating Capacity <sup>1</sup>	Net Water	AFUE <sup>1</sup>	
	Number	Min	Max	(MBH)	Ratings <sup>2</sup>	(%)	
	PF-50	16	50	47	41	95.0	
	PF-80	20	80	75	65	95.0	
RESIDENTIAL	PF-110	27.5	110	103	90	95.0	
	PF-140	35	140	131	114	95.0	
	PF-200	42	199	185	161	95.0	
	PF-210	42	210	195	170	95.1	
	Boiler Model	Input (MBH)		Gross Output	Net Water	Thermal	
	Number	Min	Max	(MBH)	Ratings <sup>2</sup>	Efficiency (%)	
COMMERCIAL	PF-300	60	300	290	252	96.5	
	<b>PF-399</b> 8		399	380	330	95.2	
	PFC-460	92	460	438	381	95.2	

Note: Consult factory before selecting a boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.

<sup>1</sup> Heating Capacity and Annual Fuel Utilization Efficiency (AFUE) ratings are based on U.S. Government test. Before purchasing this appliance, read important information about its estimated annual energy consumption or energy efficiency rating that is available from your retailer.

## **Dimensions & Connection Sizes**

	Boiler Model Number	A	В	С	D	E	F	G	н	J	К	L	м
RESIDENTIAL	PF-50/PF-80	13-3/4"	17-3/16"	29-1/2"	3-1/8"	4-13/16"	2-7/16"	4-1/2"	5-1/4"	3"	1"	N/A	N/A
	PF-110	19-3/8"	17-3/16"	29-1/2"	3-1/8"	7-5/8"	2-7/16"	4-1/2"	5-1/4"	3"	1"	N/A	N/A
	PF-140	19-3/8"	17-3/16"	29-1/2"	3-1/8"	10-1/2"	2-7/16"	4-1/2"	5-1/4"	3"	1"	N/A	N/A
	PF-200/PF-210	16-3/4"	17-3/16"	40-1/2"	1"	3"	3/4"	1-3/4"	4-1/2"	2-15/16"	6-1/2"	3-9/16"	2-1/4"
COMMERCIAL	PF-300 PF-399 PFC-460	28-1/8"	17-3/16"	40-1/2"	1-1/2"	4"	3/4"	2-11/16"	5-1/4"	3-9/16"	5-13/16"	7-1/16"	2"



PF-200, PF-210, PF-300, PF-399 & PFC-460

